



Scotch™

High Temperature Masking Tape 2310M

Product Data Sheet

Updated : July 2000
Supersedes : October 1998

Product Description

Scotch™ Tape 2310M is a chamois coloured smooth creped high temperature paper masking tape. This product is well suited for paint masking operations in the automotive market.

Applications

Scotch™ Tape 2310M is designed specifically for uses where high cure temperatures are required. This superior masking tape is able to withstand temperatures of 160 °C for one hour. It provides also outstanding results in final repair applications.

Physical Properties

Not for specification purposes
(Calipers are nominal values)

Backing	Latex Saturated Smooth Creped Paper
Adhesive	Controlled Crosslinked Rubber Resin
Shelf Life	12 months from date of manufacture by 3M when properly stored in a clean dry place at 21°C & 50 % Relative Humidity.

Product Characteristics

Not for specification purposes

Thickness AFERA4006	0.180 mm
Adhesion to Steel AFERA4001	10 N/25mm
Tensile Strength AFERA4004	120 N/25mm
Elongation AFERA4005	10%
Temperature Performance	160°C Satisfactory performance and clean removal of Scotch™ Tape 2310M will be achieved at varying temperatures/time exposure on many substrates. Tests should be conducted to establish Scotch™ Tape 2310M performance parameters in your process conditions. The optimum level for product performance and easy removal is at 160°C for 60 minutes.

Date : July 2000
 Scotch™ High Temperature
 Masking Tape 2310M

Features/Advantages/ Benefits	Features	Advantages	Benefits
	Latex Saturated Heavy Weight Creped Paper Backing	Excellent Solvent Resistance and Water Smoothness	Prevents Paint Bleed Through
		Easy Hand Tear	Reduces Finger Abrasion
		Thinness	Good Handling
		Excellent Sliver Resistance	High Quality Paint Line
		Excellent Conformability	Easy Removal
		Paint Flaking Resistance	Good Curve Masking
	Crosslinked Rubber Resin Adhesive	Instant Adhesion	Good Finished Surface
		Very Good Holding Power	Adheres Easily
		Good Adhesive Transfer Resistance	Resists Lifting
			Clean Removal

3M and Scotch are trademarks of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



Tapes & Adhesives Group

3M United Kingdom PLC
 3M House, PO Box 1,
 Market Place,
 Bracknell, Berkshire,
 RG12 1JU

Product Information :
 Tel 0870 60 800 50
 Fax 0870 60 700 99

3M Ireland
 3M House, Adelphi Centre,
 Upper Georges Street,
 Dun Laoghaire, Co. Dublin,
 Ireland

© 3M United Kingdom PLC 2000

Customer Service :
 Tel (01) 280 3555
 Fax (01) 280 3509