



Vinyl Duct Tape

3903

FOD# 1762
Page 2 of 3

Shelf Life To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Application Ideas Sealing and protecting surfaces and openings from dust, dirt and moisture. Color-coding. Temporary repairs. Non-critical masking. General maintenance activities. Wrapping and bundling. Protecting from abrasion.

Features	FEATURES	ADVANTAGES	BENEFITS
	Embossed vinyl backing	Easy to tear straight across by hand	Saves time, no additional tools needed, minimizes waste
		Excellent conformability	Conforms to the surface to which it is applied. Minimizes amount of tape needed
		Contains no cloth scrim	No exposed thread ends to wick water into the adhesive layer
		Lower unwind force	Less effort to remove tape from roll. Less user fatigue.
		Seven backing colors	Can be used for color-coding. Provides easy, on-site identification
	Natural rubber adhesive	Adhesive releases when accidentally stuck to itself	Less waste from having to throw away tangled tape
		Adhesive transfer resistance	Minimal clean up when tape is removed. Saves time and materials
	Heat resistant	Adhesive and backing will perform well and remove cleanly from surface after 1 hr. at up to 250°F	Can be used in a wide variety of applications. Less time spent on clean up

Technical Information and Data The technical information and data, recommendations, and other statements provided are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.



Vinyl Duct Tape

3903

FOD# 1762

Page 3 of 3

Product Use

Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy

The 3M product will be free from defects in material and manufacture for a period of one (1) year from the date of manufacture. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. If the 3M product is defective within the warranty period stated above, your exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, warranty, negligence, or strict liability.



This Industrial Tape and Specialties Division product was manufactured under a quality system registered to ISO 9002 standards



Industrial Tape and Specialties Division

3M Center, Building 220-7W-03
St. Paul, MN 55144-1000
USA
1 800.722.5463
1 800.223.7427 Fax On Demand
www.3M.com

Printed in U.S.A.
Copyright © 2000, 3M IPC. All rights reserved.
70-0709-4664-8